



Self-lubricating bearing series

LM UU-MX-LM10UU-MXLMU-MX10MX-LMC02-d10

参数信息:



Model No. :

YTP :	LM10UU-MX
MISUMI :	LMU-MX10
YHDA :	MX-LMC02-d10

NUMBER OF BALL ROWS :

Column :	4
----------	---

Boundary dimensions :

INSCRIBED CIRCLE DIAMETER dr :	10
INSCRIBED CIRCLE DIAMETER TOLERANCE :	0 -0.009
OUTER DIAMETER D :	19
Outer DiameterTolerance :	0 -0.013
LengthL :	39
LengthL1 :	29
LengthTolerance :	± 0.3
V :	5
LOCKING GROOVE B :	22
LOCKING GROOVE TOLERANCE :	0 -0.20
LOCKING GROOVE D1 :	18
W :	1.3
Eccentricity(MAX.) :	0.012

Basic Load Rating :

C(kgf) : 38

Co(kgf) : 56

Weight :

(g) : 35

介绍:

Model No.	Pro duc tion Stan dar ds	Outer Coving			Balls		Retainer		Seals Material	
		Material	Hardness (HRC)	Treatmen t Of Surfaces	Material	Hardness (HRC)	Material	Holder Working Temperat ure	Skeleton	Rubber
LM UU-MX	GB/ T16 940 -20 12	GCr15	60 ~ 64	-	GCr15	61 ~ 66	Resin	-20 ~ 80	65Mn	Nitrile Rubber
LM AUU-MX	GB/ T16 940 -20 12	GCr15	60 ~ 64	Electroles s Nickel Plating	GCr15	61 ~ 66	Resin	-20 ~ 80	65Mn	Nitrile Rubber

Note: The apertures of 35, 40, and 50 are not produced and are for reference only.