



Self-lubricating bearing series

LM UU-MX-LM12UU-MXLMU-MX12MX-LMC02-d12

参数信息:



Model No. :

YTP :	LM12UU-MX
MISUMI :	LMU-MX12
YHDA :	MX-LMC02-d12

NUMBER OF BALL ROWS :

Column :	4
----------	---

Boundary dimensions :

INSCRIBED CIRCLE DIAMETER dr :	12
INSCRIBED CIRCLE DIAMETER TOLERANCE :	0 -0.009
OUTER DIAMETER D :	21
Outer DiameterTolerance :	0 -0.013
LengthL :	41
LengthL1 :	30
LengthTolerance :	± 0.3
V :	5.5
LOCKING GROOVE B :	23
LOCKING GROOVE TOLERANCE :	0 -0.20
LOCKING GROOVE D1 :	20
W :	1.3
Eccentricity(MAX.) :	0.012

Basic Load Rating :

C(kgf) : 42

Co(kgf) : 61

Weight :

(g) : 45

介绍:

Model No.	Production Standards	Outer Coving			Balls		Retainer		Seals Material	
		Material	Hardness ( HRC )	Treatment Of Surfaces	Material	Hardness ( HRC )	Material	Holder Working Temperature	Skeleton	Rubber
LM UU-MX	GB/T16940-2012	GCr15	60 ~ 64	-	GCr15	61 ~ 66	Resin	-20 ~ 80	65Mn	Nitrile Rubber
LM AUU-MX	GB/T16940-2012	GCr15	60 ~ 64	Electroless Nickel Plating	GCr15	61 ~ 66	Resin	-20 ~ 80	65Mn	Nitrile Rubber

Note: The apertures of 35, 40, and 50 are not produced and are for reference only.