



Self-lubricating bearing series

LM UU-MX-**LM16UU-MX**LMU-MX16MX-LMC02-d16

参数信息:



Model No. :

YTP :	LM16UU-MX
MISUMI :	LMU-MX16
YHDA :	MX-LMC02-d16

NUMBER OF BALL ROWS :

Column :	5
----------	---

Boundary dimensions :

INSCRIBED CIRCLE DIAMETER dr :	16
INSCRIBED CIRCLE DIAMETER TOLERANCE :	0 -0.009
OUTER DIAMETER D :	28
Outer DiameterTolerance :	0 -0.013
LengthL :	49
LengthL1 :	37
LengthTolerance :	± 0.3
V :	6
LOCKING GROOVE B :	26.5
LOCKING GROOVE TOLERANCE :	0 -0.20
LOCKING GROOVE D1 :	27
W :	1.6
Eccentricity(MAX.) :	0.012

Basic Load Rating :

C(kgf) : 79

Co(kgf) : 120

Weight :

(g) : 80

介绍:

Model No.	Production Standards	Outer Coving			Balls		Retainer		Seals Material	
		Material	Hardness (HRC)	Treatment Of Surfaces	Material	Hardness (HRC)	Material	Holder Working Temperature	Skeleton	Rubber
LM UU-MX	GB/T16940-2012	GCr15	60 ~ 64	-	GCr15	61 ~ 66	Resin	-20 ~ 80	65Mn	Nitrile Rubber
LM AUU-MX	GB/T16940-2012	GCr15	60 ~ 64	Electroless Nickel Plating	GCr15	61 ~ 66	Resin	-20 ~ 80	65Mn	Nitrile Rubber

Note: The apertures of 35, 40, and 50 are not produced and are for reference only.