



Self-lubricating bearing series

LM UU-MX-**LM20UU-MX**LMU-MX20MX-LMC02-d20

参数信息:



Model No. :

YTP :	LM20UU-MX
MISUMI :	LMU-MX20
YHDA :	MX-LMC02-d20

NUMBER OF BALL ROWS :

Column :	5
----------	---

Boundary dimensions :

INSCRIBED CIRCLE DIAMETER dr :	20
INSCRIBED CIRCLE DIAMETER TOLERANCE :	0 -0.010
OUTER DIAMETER D :	32
Outer DiameterTolerance :	0 -0.016
LengthL :	56
LengthL1 :	42
LengthTolerance :	± 0.3
V :	7
LOCKING GROOVE B :	30.5
LOCKING GROOVE TOLERANCE :	0 -0.20
LOCKING GROOVE D1 :	30.5
W :	1.6
Eccentricity(MAX.) :	0.015

Basic Load Rating :

C(kgf) : 88

Co(kgf) : 140

Weight :

(g) : 109

介绍:

Model No.	Pro duc tion Stan dar ds	Outer Coving			Balls		Retainer		Seals Material	
		Material	Hardness (HRC)	Treatmen t Of Surfaces	Material	Hardness (HRC)	Material	Holder Working Temperat ure	Skeleton	Rubber
LM UU-MX	GB/ T16 940 -20 12	GCr15	60 ~ 64	-	GCr15	61 ~ 66	Resin	-20 ~ 80	65Mn	Nitrile Rubber
LM AUU-MX	GB/ T16 940 -20 12	GCr15	60 ~ 64	Electroless Nickel Plating	GCr15	61 ~ 66	Resin	-20 ~ 80	65Mn	Nitrile Rubber

Note: The apertures of 35, 40, and 50 are not produced and are for reference only.