



Self-lubricating bearing series

LM UU-MX-**LM25UU-MX**LMU-MX25MX-LMC02-d25

参数信息:



Model No. :

YTP :	LM25UU-MX
MISUMI :	LMU-MX25
YHDA :	MX-LMC02-d25

NUMBER OF BALL ROWS :

Column :	6
----------	---

Boundary dimensions :

INSCRIBED CIRCLE DIAMETER dr :	25
INSCRIBED CIRCLE DIAMETER TOLERANCE :	0 -0.010
OUTER DIAMETER D :	40
Outer DiameterTolerance :	0 -0.016
LengthL :	77
LengthL1 :	59
LengthTolerance :	± 0.3
V :	9
LOCKING GROOVE B :	41
LOCKING GROOVE TOLERANCE :	0 -0.30
LOCKING GROOVE D1 :	38
W :	1.85
Eccentricity(MAX.) :	0.015

Basic Load Rating :

C(kgf) : 100

Co(kgf) : 160

Weight :

(g) : 255

介绍:

Model No.	Pro duc tion Stan dar ds	Outer Coving			Balls		Retainer		Seals Material	
		Material	Hardness ( HRC )	Treatmen t Of Surfaces	Material	Hardness ( HRC )	Material	Holder Working Temperat ure	Skeleton	Rubber
LM UU-MX	GB/ T16 940 -20 12	GCr15	60 ~ 64	-	GCr15	61 ~ 66	Resin	-20 ~ 80	65Mn	Nitrile Rubber
LM AUU-MX	GB/ T16 940 -20 12	GCr15	60 ~ 64	Electroless Nickel Plating	GCr15	61 ~ 66	Resin	-20 ~ 80	65Mn	Nitrile Rubber

Note: The apertures of 35, 40, and 50 are not produced and are for reference only.