



Self-lubricating bearing series

LM UU-MX-LM30UU-MXLMU-MX30MX-LMC02-d30

参数信息:



Model No. :

YTP :	LM30UU-MX
MISUMI :	LMU-MX30
YHDA :	MX-LMC02-d30

NUMBER OF BALL ROWS :

Column :	6
----------	---

Boundary dimensions :

INSCRIBED CIRCLE DIAMETER dr :	30
INSCRIBED CIRCLE DIAMETER TOLERANCE :	0 -0.010
OUTER DIAMETER D :	45
Outer DiameterTolerance :	0 -0.016
LengthL :	84
LengthL1 :	64
LengthTolerance :	± 0.3
V :	10
LOCKING GROOVE B :	44.5
LOCKING GROOVE TOLERANCE :	0 -0.30
LOCKING GROOVE D1 :	43
W :	1.85
Eccentricity(MAX.) :	0.015

Basic Load Rating :

C(kgf) : 160

Co(kgf) : 220

Weight :

(g) : 286

介绍:

Model No.	Production Standards	Outer Coving			Balls		Retainer		Seals Material	
		Material	Hardness (HRC)	Treatment Of Surfaces	Material	Hardness (HRC)	Material	Holder Working Temperature	Skeleton	Rubber
LM UU-MX	GB/T16940-2012	GCr15	60 ~ 64	-	GCr15	61 ~ 66	Resin	-20 ~ 80	65Mn	Nitrile Rubber
LM AUU-MX	GB/T16940-2012	GCr15	60 ~ 64	Electroless Nickel Plating	GCr15	61 ~ 66	Resin	-20 ~ 80	65Mn	Nitrile Rubber

Note: The apertures of 35, 40, and 50 are not produced and are for reference only.