



Self-lubricating bearing series

LM UU-MX-**LM35UU-MX**LMU-MX35MX-LMC02-d35

参数信息:



Model No. :

YTP :	LM35UU-MX
MISUMI :	LMU-MX35
YHDA :	MX-LMC02-d35

NUMBER OF BALL ROWS :

Column :	6
----------	---

Boundary dimensions :

INSCRIBED CIRCLE DIAMETER dr :	35
INSCRIBED CIRCLE DIAMETER TOLERANCE :	0 -0.012
OUTER DIAMETER D :	52
Outer DiameterTolerance :	0 -0.019
LengthL :	92
LengthL1 :	70
LengthTolerance :	± 0.3
V :	11
LOCKING GROOVE B :	49.5
LOCKING GROOVE TOLERANCE :	0 -0.30
LOCKING GROOVE D1 :	49
W :	2.1
Eccentricity(MAX.) :	0.02

Basic Load Rating :

C(kgf) : 170

Co(kgf) : 320

Weight :

(g) : 453

介绍:

Model No.	Pro duc tion Stan dar ds	Outer Coving			Balls		Retainer		Seals Material	
		Material	Hardness ( HRC )	Treatmen t Of Surfaces	Material	Hardness ( HRC )	Material	Holder Working Temperat ure	Skeleton	Rubber
LM UU-MX	GB/ T16 940 -20 12	GCr15	60 ~ 64	-	GCr15	61 ~ 66	Resin	-20 ~ 80	65Mn	Nitrile Rubber
LM AUU-MX	GB/ T16 940 -20 12	GCr15	60 ~ 64	Electroles s Nickel Plating	GCr15	61 ~ 66	Resin	-20 ~ 80	65Mn	Nitrile Rubber

Note: The apertures of 35, 40, and 50 are not produced and are for reference only.