



Self-lubricating bearing series

LM UU-MX-LM40UU-MXLMU-MX40MX-LMC02-d40

参数信息:



Model No. :

YTP :	LM40UU-MX
MISUMI :	LMU-MX40
YHDA :	MX-LMC02-d40

NUMBER OF BALL ROWS :

Column :	6
----------	---

Boundary dimensions :

INSCRIBED CIRCLE DIAMETER dr :	40
INSCRIBED CIRCLE DIAMETER TOLERANCE :	0 -0.012
OUTER DIAMETER D :	60
Outer DiameterTolerance :	0 -0.019
LengthL :	104
LengthL1 :	80
LengthTolerance :	± 0.3
V :	12
LOCKING GROOVE B :	60.5
LOCKING GROOVE TOLERANCE :	0 -0.30
LOCKING GROOVE D1 :	57
W :	2.1
Eccentricity(MAX.) :	0.02

Basic Load Rating :

C(kgf) : 220

Co(kgf) : 410

Weight :

(g) : 687

介绍:

Model No.	Production Standards	Outer Coving			Balls		Retainer		Seals Material	
		Material	Hardness (HRC)	Treatment Of Surfaces	Material	Hardness (HRC)	Material	Holder Working Temperature	Skeleton	Rubber
LM UU-MX	GB/T16940-2012	GCr15	60 ~ 64	-	GCr15	61 ~ 66	Resin	-20 ~ 80	65Mn	Nitrile Rubber
LM AUU-MX	GB/T16940-2012	GCr15	60 ~ 64	Electroless Nickel Plating	GCr15	61 ~ 66	Resin	-20 ~ 80	65Mn	Nitrile Rubber

Note: The apertures of 35, 40, and 50 are not produced and are for reference only.