



Self-lubricating bearing series

LM UU-MX-LM50UU-MXLMU-MX50MX-LMC02-d50

参数信息:



Model No. :

YTP :	LM50UU-MX
MISUMI :	LMU-MX50
YHDA :	MX-LMC02-d50

NUMBER OF BALL ROWS :

Column :	6
----------	---

Boundary dimensions :

INSCRIBED CIRCLE DIAMETER dr :	50
INSCRIBED CIRCLE DIAMETER TOLERANCE :	0 -0.012
OUTER DIAMETER D :	80
Outer DiameterTolerance :	0 -0.019
LengthL :	128
LengthL1 :	100
LengthTolerance :	± 0.3
V :	14
LOCKING GROOVE B :	74
LOCKING GROOVE TOLERANCE :	0 -0.30
LOCKING GROOVE D1 :	76.5
W :	2.6
Eccentricity(MAX.) :	0.02

Basic Load Rating :

C(kgf) : 390

Co(kgf) : 810

Weight :

(g) : 1763

介绍:

Model No.	Pro duc tion Stan dar ds	Outer Coving			Balls		Retainer		Seals Material	
		Material	Hardness (HRC)	Treatmen t Of Surfaces	Material	Hardness (HRC)	Material	Holder Working Temperat ure	Skeleton	Rubber
LM UU-MX	GB/ T16 940 -20 12	GCr15	60 ~ 64	-	GCr15	61 ~ 66	Resin	-20 ~ 80	65Mn	Nitrile Rubber
LM AUU-MX	GB/ T16 940 -20 12	GCr15	60 ~ 64	Electroless Nickel Plating	GCr15	61 ~ 66	Resin	-20 ~ 80	65Mn	Nitrile Rubber

Note: The apertures of 35, 40, and 50 are not produced and are for reference only.