



Triple lengthened bearing series

LMHC TUU-LMHC35TUULHKMCNL35LMR81-d35

参数信息:



Model No. :

YTP :	LMHC35 TUU
MISUMI :	LHKMC NL35
YHDA :	LMR81-d 35

NUMBER OF BALL
ROWS :

Column :	6
----------	---

Boundary
dimensions :

INSCRIBED CIRCLE DIAMETER _{dr} :	35
INSCRIBED CIRCLE DIAMETER TOLERANCE :	0-0.021
OUTER DIAMETER _D :	60
Outer DiameterTolerance :	-
Length _L :	200
LengthTolerance :	± 0.3
I :	67
Flange _{D1} :	96
Flange _W :	66
Flange _H :	13
Flange _A :	64
Flange _F :	45
HOLE FOR ATTACHMENT _{d1} :	9
HOLE FOR ATTACHMENT _{d2} :	14
HOLE FOR	8.1

ATTACHMENTh :

SOUAR- ENESS : 0.03

Eccentricity (MAX.) : 0.03

Basic Load Rating :

C(kgf) : 270

Co(kgf) : 640

Weight :

(g) : 2433

介绍:

Model	Producti on standard	Shell			rolling ball		Retainer		Accessory (seal) material		
		Material	Hardness (HRC)	Surface treatment	Material	Hardness (HRC)	Material	Using te mperatur e	Skeleton	Rubber	
LMHC TUU	GB/T169 40-2012	GCr15	60 ~ 64	-	GCr15	61 ~ 66	Resin	-20 ~ 80	65Mn	Nitrile rubber	
LMHC TAUU	GB/T169 40-2012	GCr15	60 ~ 64	Electroless nickel plating	GCr15	61 ~ 66	Resin	-20 ~ 80	65Mn	Nitrile rubber	
LMHC TM	GB/T169 40-2012	GCr15	60 ~ 64	-	GCr15	61 ~ 66	304 stainless steel	-20 ~ 80	65Mn	-	
LMHC TAM	GB/T169 40-2012	GCr15	60 ~ 64	Electroless nickel plating	GCr15	61 ~ 66	304 stainless steel	-20 ~ 80	65Mn	-	

Note: The inner holes are 6, 8, 10, 13, 35, 40, not produced, for reference only.