



Triple lengthened bearing series

LMHC TUU-LMHC16TUULHKMCNL16LMR81-d16

参数信息:



Model No. :

YTP :	LMHC16 TUU
MISUMI :	LHKMC NL16
YHDA :	LMR81-d 16

NUMBER OF BALL  
ROWS :

Column :	5
----------	---

Boundary  
dimensions :

INSCRIBED CIRCLE DIAMETER <sub>dr</sub> :	16
INSCRIBED CIRCLE DIAMETER TOLERANCE :	0-0.015
OUTER DIAMETER <sub>D</sub> :	32
Outer DiameterTolerance :	0-0.019
Length <sub>L</sub> :	105
LengthTolerance :	± 0.3
I :	35
Flange <sub>D1</sub> :	54
Flange <sub>W</sub> :	38
Flange <sub>H</sub> :	8
Flange <sub>A</sub> :	36
Flange <sub>F</sub> :	24
HOLE FOR ATTACHMENT <sub>d1</sub> :	5.5
HOLE FOR ATTACHMENT <sub>d2</sub> :	9
HOLE FOR	5.1

ATTACHMENTh :

SOUAR- ENESS : 0.025

Eccentricity (MAX.) : 0.025

Basic Load Rating :

C(kgf) : 126

Co(kgf) : 240

Weight :

(g) : 386

介绍:

Model	Producti on standard	Shell			rolling ball		Retainer		Accessory (seal) material		
		Material	Hardness (HRC)	Surface treatment	Material	Hardness (HRC)	Material	Using te mperatur e	Skeleton	Rubber	
LMHC TUU	GB/T169 40-2012	GCr15	60 ~ 64	-	GCr15	61 ~ 66	Resin	-20 ~ 80	65Mn	Nitrile rubber	
LMHC TAUU	GB/T169 40-2012	GCr15	60 ~ 64	Electroless nickel plating	GCr15	61 ~ 66	Resin	-20 ~ 80	65Mn	Nitrile rubber	
LMHC TM	GB/T169 40-2012	GCr15	60 ~ 64	-	GCr15	61 ~ 66	304 stainless steel	-20 ~ 80	65Mn	-	
LMHC TAM	GB/T169 40-2012	GCr15	60 ~ 64	Electroless nickel plating	GCr15	61 ~ 66	304 stainless steel	-20 ~ 80	65Mn	-	

Note: The inner holes are 6, 8, 10, 13, 35, 40, not produced, for reference only.