



Triple lengthened bearing series

LMHC TUU-LMHC25TUULHKMCNL25LMR81-d25

参数信息:



Model No. :

YTP :	LMHC25 TUU
MISUMI :	LHKMC NL25
YHDA :	LMR81-d 25

NUMBER OF BALL
ROWS :

Column :	6
----------	---

Boundary
dimensions :

INSCRIBED CIRCLE DIAMETER _{dr} :	25
INSCRIBED CIRCLE DIAMETER TOLERANCE :	0-0.018
OUTER DIAMETER _D :	45
Outer DiameterTolerance :	0-0.019
Length _L :	167
LengthTolerance :	± 0.3
I :	55
Flange _{D1} :	74
Flange _W :	51
Flange _H :	10
Flange _A :	49
Flange _F :	35
HOLE FOR ATTACHMENT _{d1} :	6.6
HOLE FOR ATTACHMENT _{d2} :	11
HOLE FOR	6.1

ATTACHMENTh :

SOUAR- ENESS : 0.025

Eccentricity (MAX.) : 0.025

Basic Load Rating :

C(kgf) : 159

Co(kgf) : 320

Weight :

(g) : 1178

介绍:

Model	Producti on standard	Shell			rolling ball		Retainer		Accessory (seal) material		
		Material	Hardness (HRC)	Surface treatment	Material	Hardness (HRC)	Material	Using te mperatur e	Skeleton	Rubber	
LMHC TUU	GB/T169 40-2012	GCr15	60 ~ 64	-	GCr15	61 ~ 66	Resin	-20 ~ 80	65Mn	Nitrile rubber	
LMHC TAUU	GB/T169 40-2012	GCr15	60 ~ 64	Electroless nickel plating	GCr15	61 ~ 66	Resin	-20 ~ 80	65Mn	Nitrile rubber	
LMHC TM	GB/T169 40-2012	GCr15	60 ~ 64	-	GCr15	61 ~ 66	304 stainless steel	-20 ~ 80	65Mn	-	
LMHC TAM	GB/T169 40-2012	GCr15	60 ~ 64	Electroless nickel plating	GCr15	61 ~ 66	304 stainless steel	-20 ~ 80	65Mn	-	

Note: The inner holes are 6, 8, 10, 13, 35, 40, not produced, for reference only.