



Linear bearing standard series

LM UU-AJ -LM25UU-AJLMC41-d25SM25GUU-AJ

参数信息:



model :

YTP (Resin Retainer) :	LM25UU-AJ
YTP (Steel Protection) :	LM25M-AJ
YHDA :	LMC41-d25
NB :	SM25GUU-AJ
SAMICK :	LM25UU-AJ

Number of Ball Columns :

column : 6

weight :

( g ) : 216

Main dimensions :

Inner diameter dr :	25
Inner diameter tolerance :	0 -0.010
Outer diameter D :	40
Outer diameter tolerance :	0 -0.016
Length L :	59
Length tolerance :	0 -0.30
External stop groove B :	41
Outer stop groove tolerance :	0 -0.30
External stop groove D1 :	38
W :	1.85
h :	2

Radial runout(MAX.) : 0.015

Basic rated load :  
C(kgf) : 100  
Co(kgf) : 160

介绍:

Model	Producti on standard	Shell			rolling ball		Retainer		Accessory (seal) material	
		Material	Hardness (HRC)	Surface treatment	Material	Hardness (HRC)	Material	Using te mperatur e	Skeleton	Rubber
LM UU-AJ	GB/T169 40-2012	GCr15	60 ~ 64	-	GCr15	61 ~ 66	Resin	-20 ~ 80	65Mn	Nitrile rubber
LM AUU-AJ	GB/T169 40-2012	GCr15	60 ~ 64	Electroless nickel plating	GCr15	61 ~ 66	Resin	-20 ~ 80	65Mn	Nitrile rubber
LM M-AJ	GB/T169 40-2012	GCr15	60 ~ 64	-	GCr15	61 ~ 66	304 stainless steel	-20 ~ 150	65Mn	-
LM AM-AJ	GB/T169 40-2012	GCr15	60 ~ 64	Electroless nickel plating	GCr15	61 ~ 66	304 stainless steel	-20 ~ 150	65Mn	-