




Linear flange bearing series

LMHP □ M-LMHP35MLHIFCF35

参数信息:



Model No. :

YTP (Steel Protection) :	LMHP35 M
MISUMI (Steel Insurance) :	LHIFCF3 5

NUMBER OF BALL ROWS :

Column : 6

Weight :

(g) : 590

Boundary dimensions :

INSCRIBED CIRCLE DIAMETER dr :	35
Inscribed Circle DiameterTolerance :	0 -0.012
OUTER DIAMETERD :	52
Outer DiameterTolerance :	0 -0.022
Length L :	70
LENGTH TOLERANCE :	± 0.3
I :	10
Flange D1 :	82
Flange W :	58
Flange H :	10
FLRNGE A :	55
FlangeF :	38
HOLE FOR ATTACHMENT d1 :	6.6
HOLE FOR ATTACHMENT d2 :	11

HOLE FOR ATTACHMENT h :	6.1
SOUAR- ENESS :	0.02
Eccentricity (MAX.) :	0.02

Basic Load Rating :

C(kgf) :	170
Co(kgf) :	320

介绍:

Model	Production standard	Shell			rolling ball		Retainer		Accessory (seal) material	
		Material	Hardness (HRC)	Surface treatment	Material	Hardness (HRC)	Material	Using temperature	Skeleton	Rubber
LMHP □ UU	GB/T16940-2012	GCr15	60 ~ 64	-	GCr15	61 ~ 66	Resin	-20 ~ 80	65Mn	Nitrile rubber
LMHP □ AUU	GB/T16940-2012	GCr15	60 ~ 64	Electroless nickel plating	GCr15	61 ~ 66	Resin	-20 ~ 80	65Mn	Nitrile rubber
LMHP □ M	GB/T16940-2012	GCr15	60 ~ 64	-	GCr15	61 ~ 66	304 stainless steel	-20 ~ 150	65Mn	-
LMHP □ AM	GB/T16940-2012	GCr15	60 ~ 64	Electroless nickel plating	GCr15	61 ~ 66	304 stainless steel	-20 ~ 150	65Mn	-

Note: The inner diameter 6 retainer is made of carbon steel (08F) and the inner diameter 13 is not produced, and is for reference only.