




Linear flange bearing series

LMHP □ M-LMHP40MLHIFCF40

参数信息:



Model No. :

YTP (Steel Protection) :	LMHP40 M
MISUMI (Steel Insurance) :	LHIFCF4 0

NUMBER OF BALL ROWS :

Column :	6
----------	---

Weight :

(g) :	910
-------	-----

Boundary dimensions :

INSCRIBED CIRCLE DIAMETER dr :	40
Inscribed Circle DiameterTolerance :	0 -0.012
OUTER DIAMETERD :	60
Outer DiameterTolerance :	0 -0.022
Length L :	80
LENGTH TOLERANCE :	±0.3
I :	13
Flange D1 :	96
Flange W :	66
Flange H :	13
FLRNGE A :	64
FlangeF :	45
HOLE FOR ATTACHMENT d1 :	9
HOLE FOR ATTACHMENT d2 :	14

HOLE FOR ATTACHMENT h : 8.1

SOUAR- ENESS : 0.02

Eccentricity (MAX.) : 0.02

Basic Load Rating :

C(kgf) : 220

Co(kgf) : 410

介绍:

Model	Production standard	Shell			rolling ball		Retainer		Accessory (seal) material	
		Material	Hardness (HRC)	Surface treatment	Material	Hardness (HRC)	Material	Using temperature °C	Skeleton	Rubber
LMHP □ UU	GB/T16940-2012	GCr15	60~64	-	GCr15	61~66	Resin	-20~80	65Mn	Nitrile rubber
LMHP □ AUU	GB/T16940-2012	GCr15	60~64	Electroless nickel plating	GCr15	61~66	Resin	-20~80	65Mn	Nitrile rubber
LMHP □ M	GB/T16940-2012	GCr15	60~64	-	GCr15	61~66	304 stainless steel	-20~150	65Mn	-
LMHP □ AM	GB/T16940-2012	GCr15	60~64	Electroless nickel plating	GCr15	61~66	304 stainless steel	-20~150	65Mn	-

Note: The inner diameter 6 retainer is made of carbon steel (08F) and the inner diameter 13 is not produced, and is for reference only.