




Linear flange bearing series

LMHP □ M-LMHP8MLHIFCF8

参数信息:



Model No. :

YTP (Steel Protection) :	LMHP8M
MISUMI (Steel Insurance) :	LHIFCF8

NUMBER OF BALL ROWS :

Column : 4

Weight :

(g) : 33

Boundary dimensions :

INSCRIBED CIRCLE DIAMETER dr :	8
Inscribed Circle DiameterTolerance :	0 -0.009
OUTER DIAMETERD :	15
Outer DiameterTolerance :	0 -0.013
Length L :	24
LENGTH TOLERANCE :	±0.3
I :	5
Flange D1 :	32
Flange W :	21
Flange H :	5
FLRNGE A :	24
FlangeF :	
HOLE FOR ATTACHMENT d1 :	3.5
HOLE FOR ATTACHMENT d2 :	6

HOLE FOR ATTACHMENT h :	3.1
-------------------------	-----

SOUAR- ENESS :	0.012
----------------	-------

Eccentricity (MAX.) :	0.012
-----------------------	-------

Basic Load Rating :	
---------------------	--

C(kgf) :	27
----------	----

Co(kgf) :	41
-----------	----

介绍:

Model	Production standard	Shell			rolling ball		Retainer		Accessory (seal) material	
		Material	Hardness (HRC)	Surface treatment	Material	Hardness (HRC)	Material	Using temperature °C	Skeleton	Rubber
LMHP □ UU	GB/T16940-2012	GCr15	60~64	-	GCr15	61~66	Resin	-20~80	65Mn	Nitrile rubber
LMHP □ AUU	GB/T16940-2012	GCr15	60~64	Electroless nickel plating	GCr15	61~66	Resin	-20~80	65Mn	Nitrile rubber
LMHP □ M	GB/T16940-2012	GCr15	60~64	-	GCr15	61~66	304 stainless steel	-20~150	65Mn	-
LMHP □ AM	GB/T16940-2012	GCr15	60~64	Electroless nickel plating	GCr15	61~66	304 stainless steel	-20~150	65Mn	-

Note: The inner diameter 6 retainer is made of carbon steel (08F) and the inner diameter 13 is not produced, and is for reference only.