




Linear flange bearing series

LMHP □ M-LMHP10MLHIFCF10

参数信息:



Model No. :

YTP (Steel Protection) :	LMHP10 M
MISUMI (Steel Insurance) :	LHIFCF1 0

NUMBER OF BALL ROWS :

Column : 4

Weight :

(g) : 64

Boundary dimensions :

INSCRIBED CIRCLE DIAMETER dr :	10
Inscribed Circle DiameterTolerance :	0 -0.009
OUTER DIAMETERD :	19
Outer DiameterTolerance :	0 -0.016
Length L :	29
LENGTH TOLERANCE :	±0.3
I :	6
Flange D1 :	40
Flange W :	25
Flange H :	6
FLRNGE A :	29
FlangeF :	
HOLE FOR ATTACHMENT d1 :	4.5
HOLE FOR ATTACHMENT d2 :	7.5

HOLE FOR ATTACHMENT h : 4.1

SOUAR- ENESS : 0.012

Eccentricity (MAX.) : 0.012

Basic Load Rating :

C(kgf) : 38

Co(kgf) : 56

介绍:

Model	Production standard	Shell			rolling ball		Retainer		Accessory (seal) material	
		Material	Hardness (HRC)	Surface treatment	Material	Hardness (HRC)	Material	Using temperature °C	Skeleton	Rubber
LMHP □ UU	GB/T16940-2012	GCr15	60~64	-	GCr15	61~66	Resin	-20~80	65Mn	Nitrile rubber
LMHP □ AUU	GB/T16940-2012	GCr15	60~64	Electroless nickel plating	GCr15	61~66	Resin	-20~80	65Mn	Nitrile rubber
LMHP □ M	GB/T16940-2012	GCr15	60~64	-	GCr15	61~66	304 stainless steel	-20~150	65Mn	-
LMHP □ AM	GB/T16940-2012	GCr15	60~64	Electroless nickel plating	GCr15	61~66	304 stainless steel	-20~150	65Mn	-

Note: The inner diameter 6 retainer is made of carbon steel (08F) and the inner diameter 13 is not produced, and is for reference only.