




Linear flange bearing series

LMHP □ M-LMHP20MLHIFCF20

参数信息:



Model No. :

YTP (Steel Protection) :	LMHP20 M
MISUMI (Steel Insurance) :	LHIFCF2 0

NUMBER OF BALL ROWS :

Column : 5

Weight :

(g) : 167

Boundary dimensions :

INSCRIBED CIRCLE DIAMETER dr :	20
Inscribed Circle DiameterTolerance :	0 -0.010
OUTER DIAMETERD :	32
Outer DiameterTolerance :	0 -0.019
Length L :	42
LENGTH TOLERANCE :	± 0.3
I :	8
Flange D1 :	54
Flange W :	38
Flange H :	8
FLRNGE A :	36
FlangeF :	24
HOLE FOR ATTACHMENT d1 :	5.5
HOLE FOR ATTACHMENT d2 :	9

HOLE FOR ATTACHMENT h :	5.1
SOUAR- ENESS :	0.015
Eccentricity (MAX.) :	0.015
Basic Load Rating :	
C(kgf) :	88
Co(kgf) :	140

介绍:

Model	Production standard	Shell			rolling ball		Retainer		Accessory (seal) material	
		Material	Hardness (HRC)	Surface treatment	Material	Hardness (HRC)	Material	Using temperature	Skeleton	Rubber
LMHP □ UU	GB/T16940-2012	GCr15	60 ~ 64	-	GCr15	61 ~ 66	Resin	-20 ~ 80	65Mn	Nitrile rubber
LMHP □ AUU	GB/T16940-2012	GCr15	60 ~ 64	Electroless nickel plating	GCr15	61 ~ 66	Resin	-20 ~ 80	65Mn	Nitrile rubber
LMHP □ M	GB/T16940-2012	GCr15	60 ~ 64	-	GCr15	61 ~ 66	304 stainless steel	-20 ~ 150	65Mn	-
LMHP □ AM	GB/T16940-2012	GCr15	60 ~ 64	Electroless nickel plating	GCr15	61 ~ 66	304 stainless steel	-20 ~ 150	65Mn	-

Note: The inner diameter 6 retainer is made of carbon steel (08F) and the inner diameter 13 is not produced, and is for reference only.