




Linear flange bearing series

LMHP □ M-LMHP30MLHIFCF30

参数信息:



Model No. :

YTP (Steel Protection) :	LMHP30 M
MISUMI (Steel Insurance) :	LHIFCF3 0

NUMBER OF BALL ROWS :

Column :	6
----------	---

Weight :

(g) :	388
-------	-----

Boundary dimensions :

INSCRIBED CIRCLE DIAMETER dr :	30
Inscribed Circle DiameterTolerance :	0 -0.010
OUTER DIAMETERD :	45
Outer DiameterTolerance :	0 -0.019
Length L :	64
LENGTH TOLERANCE :	±0.3
I :	10
Flange D1 :	74
Flange W :	51
Flange H :	10
FLRNGE A :	49
FlangeF :	35
HOLE FOR ATTACHMENT d1 :	6.6
HOLE FOR ATTACHMENT d2 :	11

HOLE FOR ATTACHMENT h : 6.1

SOUAR- ENESS : 0.015

Eccentricity (MAX.) : 0.015

Basic Load Rating :

C(kgf) : 160

Co(kgf) : 280

介绍:

Model	Production standard	Shell			rolling ball		Retainer		Accessory (seal) material	
		Material	Hardness (HRC)	Surface treatment	Material	Hardness (HRC)	Material	Using temperature °C	Skeleton	Rubber
LMHP □ UU	GB/T16940-2012	GCr15	60~64	-	GCr15	61~66	Resin	-20~80	65Mn	Nitrile rubber
LMHP □ AUU	GB/T16940-2012	GCr15	60~64	Electroless nickel plating	GCr15	61~66	Resin	-20~80	65Mn	Nitrile rubber
LMHP □ M	GB/T16940-2012	GCr15	60~64	-	GCr15	61~66	304 stainless steel	-20~150	65Mn	-
LMHP □ AM	GB/T16940-2012	GCr15	60~64	Electroless nickel plating	GCr15	61~66	304 stainless steel	-20~150	65Mn	-

Note: The inner diameter 6 retainer is made of carbon steel (08F) and the inner diameter 13 is not produced, and is for reference only.