



Linear flange bearing series

LMFP □ LAUU-**LMFP20LAUULHIRWM20LML02-d20SMF20GWUU-E-SKLMFP20LUU-N**

参数信息:



Model No. :

YTP (nickel plated) :	LMFP20L AUU
MISUMI (nickel plated) :	LHIRWM 20
YHDA (nickel plated) :	LML02-d2 0
NB (nickel plated) :	SMF20G WUU-E- SK
SAMICK (nickel plating) :	LMFP20L UU-N

NUMBER OF BALL
ROWS :

Column :	5
Weight :	
(g) :	260

Boundary
dimensions :

INSCRIBED CIRCLE DIAMETER dr :	20
Inscribed Circle DiameterTolerance :	0 -0.012
OUTER DIAMETERD :	32
Outer DiameterTolerance :	0 -0.019
Length L :	80
LENGTH TOLERANCE :	± 0.3
I :	8
Flange D1 :	54
Flange K :	42
Flange H :	8

Flange Φ :	43
HOLE FOR ATTACHMENT d1 :	5.5
HOLE FOR ATTACHMENT d2 :	9
HOLE FOR ATTACHMENT h :	5.1
SOUAR- ENESS :	0.015
Eccentricity (MAX.) :	0.015

Basic Load Rating :

C(kgf) :	143
Co(kgf) :	280

介绍:

Model	Production standard	Shell			rolling ball		Retainer		Accessory (seal) material	
		Material	Hardness (HRC)	Surface treatment	Material	Hardness (HRC)	Material	Using temperature	Skeleton	Rubber
LMFP □ LUU	GB/T16940-2012	GCr15	60 ~ 64	-	GCr15	61 ~ 66	Resin	-20 ~ 80	65Mn	Nitrile rubber
LMFP □ LAUU	GB/T16940-2012	GCr15	60 ~ 64	Electroless nickel plating	GCr15	61 ~ 66	Resin	-20 ~ 80	65Mn	Nitrile rubber
LMFP □ LM	GB/T16940-2012	GCr15	60 ~ 64	-	GCr15	61 ~ 66	304 stainless steel	-20 ~ 150	65Mn	-
LMFP □ LAM	GB/T16940-2012	GCr15	60 ~ 64	Electroless nickel plating	GCr15	61 ~ 66	304 stainless steel	-20 ~ 150	65Mn	-