



Linear flange bearing series

LMFP □ LAUU -LMFP25LAUULHIRWM25LML02-d25SMF25GWUU-E-SKLMFP25LUU-N

参数信息:



Model No. :

YTP (nickel plated) :	LMFP25L AUU
MISUMI (nickel plated) :	LHIRWM 25
YHDA (nickel plated) :	LML02-d2 5
NB (nickel plated) :	SMF25G WUU-E- SK
SAMICK (nickel plating) :	LMFP25L UU-N

NUMBER OF BALL
ROWS :

Column :	6
----------	---

Weight :

(g) :	540
-------	-----

Boundary
dimensions :

INSCRIBED CIRCLE DIAMETER dr :	25
Inscribed Circle DiameterTolerance :	0 -0.012
OUTER DIAMETERD :	40
Outer DiameterTolerance :	0 -0.019
Length L :	112
LENGTH TOLERANCE :	±0.3
I :	8
Flange D1 :	62
Flange K :	50
Flange H :	8

Flange Φ : 51HOLE FOR
ATTACHMENT d1 : 5.5HOLE FOR
ATTACHMENT d2 : 9HOLE FOR
ATTACHMENT h : 5.1

SOUAR- ENESS : 0.02

Eccentricity (MAX.) : 0.02

Basic Load Rating :

C(kgf) : 159

Co(kgf) : 320

介绍:

Model	Production standard	Shell			rolling ball		Retainer		Accessory (seal) material	
		Material	Hardness (HRC)	Surface treatment	Material	Hardness (HRC)	Material	Using temperature °C	Skeleton	Rubber
LMFP □ LUU	GB/T16940-2012	GCr15	60~64	-	GCr15	61~66	Resin	-20~80	65Mn	Nitrile rubber
LMFP □ LAUU	GB/T16940-2012	GCr15	60~64	Electroless nickel plating	GCr15	61~66	Resin	-20~80	65Mn	Nitrile rubber
LMFP □ LM	GB/T16940-2012	GCr15	60~64	-	GCr15	61~66	304 stainless steel	-20~150	65Mn	-
LMFP □ LAM	GB/T16940-2012	GCr15	60~64	Electroless nickel plating	GCr15	61~66	304 stainless steel	-20~150	65Mn	-