



Linear flange bearing series

LMFP □ LAUU-**LMFP30LAUULHIRWM30LML02-d30SMF30GWUU-E-SKLMFP30LUU-N**

参数信息:



Model No. :

YTP (nickel plated) :	LMFP30L AUU
MISUMI (nickel plated) :	LHIRWM 30
YHDA (nickel plated) :	LML02-d3 0
NB (nickel plated) :	SMF30G WUU-E- SK
SAMICK (nickel plating) :	LMFP30L UU-N

NUMBER OF BALL
ROWS :

Column :	6
Weight :	
(g) :	680

Boundary
dimensions :

INSCRIBED CIRCLE DIAMETER dr :	30
Inscribed Circle DiameterTolerance :	0 -0.012
OUTER DIAMETERD :	45
Outer DiameterTolerance :	0 -0.019
Length L :	123
LENGTH TOLERANCE :	± 0.3
I :	10
Flange D1 :	74
Flange K :	58
Flange H :	10

Flange Φ : 60

HOLE FOR
ATTACHMENT d1 : 6.6

HOLE FOR
ATTACHMENT d2 : 11

HOLE FOR
ATTACHMENT h : 6.1

SOUAR- ENESS : 0.02

Eccentricity (MAX.) : 0.02

Basic Load Rating :

C(kgf) : 254

Co(kgf) : 560

介绍:

Model	Production standard	Shell			rolling ball		Retainer		Accessory (seal) material	
		Material	Hardness (HRC)	Surface treatment	Material	Hardness (HRC)	Material	Using temperature	Skeleton	Rubber
LMFP □ LUU	GB/T16940-2012	GCr15	60 ~ 64	-	GCr15	61 ~ 66	Resin	-20 ~ 80	65Mn	Nitrile rubber
LMFP □ LAUU	GB/T16940-2012	GCr15	60 ~ 64	Electroless nickel plating	GCr15	61 ~ 66	Resin	-20 ~ 80	65Mn	Nitrile rubber
LMFP □ LM	GB/T16940-2012	GCr15	60 ~ 64	-	GCr15	61 ~ 66	304 stainless steel	-20 ~ 150	65Mn	-
LMFP □ LAM	GB/T16940-2012	GCr15	60 ~ 64	Electroless nickel plating	GCr15	61 ~ 66	304 stainless steel	-20 ~ 150	65Mn	-