



Linear bearing standard series

LM LUU-LM40LUULMUW40LMC12-d40SM40GWUU

参数信息:



model :

YTP (Resin Retainer) :	LM40LU U
YTP (Steel Protection) :	LM40LM
MISUMI :	LMUW40
YHDA :	LMC12-d 40
NB :	SM40GW UU
SAMICK :	LM40LU U

Number of Ball Columns :

column : 6

weight :

(g) : 1170

Main dimensions :

Inner diameter dr :	40
Inner diameter tolerance :	0 -0.015
Outer diameter D :	60
Outer diameter tolerance :	0 -0.022
Length L :	151
Length tolerance :	0 -0.40
External stop groove B :	121
Outer stop groove tolerance :	0 -0.40
External stop groove D1 :	57
W :	2.1

Radial runout(MAX.) : 0.025

Basic rated load :

C(kgf) : 350
Co(kgf) : 820

介绍:

Model	Production standard	Shell			rolling ball		Retainer		Accessory (seal) material	
		Material	Hardness (HRC)	Surface treatment	Material	Hardness (HRC)	Material	Using temperature	Skeleton	Rubber
LM L	GB/T16940-2012	GCr15	60 ~ 64	-	GCr15	61 ~ 66	resin	-20 ~ 150	65Mn	-
LM LUU	GB/T16940-2012	GCr15	60 ~ 64	-	GCr15	61 ~ 66	Resin	-20 ~ 80	65Mn	Nitrile rubber
LM LAUU	GB/T16940-2012	GCr15	60 ~ 64	Electroless nickel plating	GCr15	61 ~ 66	Resin	-20 ~ 80	65Mn	Nitrile rubber
LM LM	GB/T16940-2012	GCr15	60 ~ 64	-	GCr15	61 ~ 66	304 stainless steel	-20 ~ 150	65Mn	-
LM LAM	GB/T16940-2012	GCr15	60 ~ 64	Electroless nickel plating	GCr15	61 ~ 66	304 stainless steel	-20 ~ 150	65Mn	-