



Linear flange bearing series

LMHC LAM-LMHC20LAM|LHMCWMF20

参数信息:



Model No. :

YTP (steel protection nickel plating) :	LMHC20 LAM
MISUMI (steel protection nickel plating) :	LHMCW MF20

NUMBER OF BALL ROWS :

Column :	5
Weight :	
(g) :	247

Boundary dimensions :

INSCRIBED CIRCLE DIAMETER dr :	20
Inscribed Circle DiameterTolerance :	0 -0.012
OUTER DIAMETERD :	32
Outer DiameterTolerance :	0 -0.019
Length L :	80
LENGTH TOLERANCE :	± 0.3
l :	36
Flange D1 :	54
FLRNGE W :	38
Flange H :	8
FLRNGE A :	36
FLRNGE F :	24
HOLE FOR ATTACHMENT d1 :	5.5
HOLE FOR ATTACHMENT d2 :	9

HOLE FOR ATTACHMENT h :	5.1
SOUAR- ENESS :	0.02
Eccentricity (MAX.) :	0.02
Basic Load Rating :	
C(kgf) :	143
Co(kgf) :	280

介绍:

Model	Production standard	Shell			rolling ball		Retainer		Accessory (seal) material	
		Material	Hardness (HRC)	Surface treatment	Material	Hardness (HRC)	Material	Using temperature	Skeleton	Rubber
LMHC LUU	GB/T16940-2012	GCr15	60 ~ 64	-	GCr15	61 ~ 66	Resin	-20 ~ 80	65Mn	Nitrile rubber
LMHC LAUU	GB/T16940-2012	GCr15	60 ~ 64	Electroless nickel plating	GCr15	61 ~ 66	Resin	-20 ~ 80	65Mn	Nitrile rubber
LMHC LM	GB/T16940-2012	GCr15	60 ~ 64	-	GCr15	61 ~ 66	304 stainless steel	-20 ~ 150	65Mn	-
LMHC LAM	GB/T16940-2012	GCr15	60 ~ 64	Electroless nickel plating	GCr15	61 ~ 66	304 stainless steel	-20 ~ 150	65Mn	-

Note: The inner diameter 6 retainer is made of carbon steel (08F) and the inner diameter 13 is not produced, and is for reference only.