



Linear flange bearing series

LMHC LAM-LMHC30LAM|LHMCWMF30

参数信息:



Model No. :

YTP (steel protection nickel plating) :	LMHC30 LAM
MISUMI (steel protection nickel plating) :	LHMCW MF30

NUMBER OF BALL ROWS :

Column : 6

Weight :

(g) : 645

Boundary dimensions :

INSCRIBED CIRCLE DIAMETER dr :	30
Inscribed Circle Diameter Tolerance :	0 -0.012
OUTER DIAMETER D :	45
Outer Diameter Tolerance :	0 -0.019
Length L :	123
LENGTH TOLERANCE :	± 0.3
l :	56.5
Flange D1 :	74
FLRNGE W :	51
Flange H :	10
FLRNGE A :	49
FLRNGE F :	35
HOLE FOR ATTACHMENT d1 :	6.6
HOLE FOR ATTACHMENT d2 :	11

HOLE FOR ATTACHMENT h :	6.1
SOUAR- ENESS :	0.02
Eccentricity (MAX.) :	0.02
Basic Load Rating :	
C(kgf) :	254
Co(kgf) :	560

介绍:

Model	Production standard	Shell			rolling ball		Retainer		Accessory (seal) material	
		Material	Hardness (HRC)	Surface treatment	Material	Hardness (HRC)	Material	Using temperature	Skeleton	Rubber
LMHC LUU	GB/T16940-2012	GCr15	60 ~ 64	-	GCr15	61 ~ 66	Resin	-20 ~ 80	65Mn	Nitrile rubber
LMHC LAUU	GB/T16940-2012	GCr15	60 ~ 64	Electroless nickel plating	GCr15	61 ~ 66	Resin	-20 ~ 80	65Mn	Nitrile rubber
LMHC LM	GB/T16940-2012	GCr15	60 ~ 64	-	GCr15	61 ~ 66	304 stainless steel	-20 ~ 150	65Mn	-
LMHC LAM	GB/T16940-2012	GCr15	60 ~ 64	Electroless nickel plating	GCr15	61 ~ 66	304 stainless steel	-20 ~ 150	65Mn	-

Note: The inner diameter 6 retainer is made of carbon steel (08F) and the inner diameter 13 is not produced, and is for reference only.