



Medium Bearing Series

LM □ RAUU-LM6RAUULMUDM6LMD12-d6

参数信息:



Model No. :

YTP (nickel plated) : LM6RAU
U

MISUMI (nickel
plated) : LMUDM
6

YHDA (nickel
plated) : LMD12-d
6

NUMBER OF BALL
ROWS :

Column : 4

Boundary
dimensions :

INSCRIBED CIRCLE
DIAMETER_{dr} : 6

INSCRIBED CIRCLE
DIAMETER
TOLERANCE : 0-0.010

OUTER
DIAMETER_D : 12

Outer
DiameterTolerance : 0-0.013

Length_L : 29

LengthTolerance : ± 0.3

OUTER LOCKING
GROOVE_B : 22.2

OUTER LOCKING G
ROOVE_{TOLERANCE}
:

OUTER LOCKING
GROOVE_{D1} : 11.5

W : 1.1

Radial
runout(MAX.) : 0.015

Basic Load Rating :

C(kgf) : 22.6

Co(kgf) : 31

Weight :

(g) : 12

介绍:

Model No.	Producti on Standards	Outer Coving			Balls		Retainer		Seals Material	
		Material	Hardness (HRC)	Treatmen t Of Surfaces	Material	Hardness (HRC)	Material	Holder Working Temperature	Skele ton	Rub ber
LM □ RUU	GB/T169 40-2012	GCr15	60 ~ 64	-	GCr15	61 ~ 66	Resin	-20 ~ 80	65M n	Nitr ile Rub ber
LM □ RAUU	GB/T169 40-2012	GCr15	60 ~ 64	Electroles s Nickel Plating	GCr15	61 ~ 66	Resin	-20 ~ 80	65M n	Nitr ile Rub ber