



Medium Bearing Series

LM RAUU-LM10RAUULMUDM10LMD12-d10

参数信息:



Model No. :

YTP (nickel plated) :	LM10RA UU
MISUMI (nickel plated) :	LMUDM 10
YHDA (nickel plated) :	LMD12-d 10

NUMBER OF BALL  
ROWS :

Column :	4
----------	---

Boundary  
dimensions :

INSCRIBED CIRCLE DIAMETER <sub>dr</sub> :	10
--	----

INSCRIBED CIRCLE DIAMETER TOLERANCE :	0-0.010
---	---------

OUTER DIAMETER <sub>D</sub> :	19
----------------------------------	----

Outer DiameterTolerance :	0-0.016
------------------------------	---------

Length <sub>L</sub> :	47
-----------------------	----

LengthTolerance :	± 0.3
-------------------	-------

OUTER LOCKING GROOVE <sub>B</sub> :	32.6
--	------

OUTER LOCKING G ROOVE <sub>TOLERANCE</sub> :	0-0.30
--	--------

OUTER LOCKING GROOVE <sub>D1</sub> :	18
---	----

W :	1.3
-----	-----

Radial runout(MAX.) :	0.015
--------------------------	-------

Basic Load Rating :

C(kgf) :	50.8
----------	------

Co(kgf) : 71.8

Weight :

(g) : 49

介绍:

Model No.	Producti on Standards	Outer Coving			Balls		Retainer		Seals Material	
		Material	Hardness ( HRC )	Treatmen t Of Surfaces	Material	Hardness ( HRC )	Material	Holder Working Temperature	Skele ton	Rub ber
LM RUU	GB/T169 40-2012	GCr15	60 ~ 64	-	GCr15	61 ~ 66	Resin	-20 ~ 80	65M n	Nitr ile Rub ber
LM RAUU	GB/T169 40-2012	GCr15	60 ~ 64	Electroles s Nickel Plating	GCr15	61 ~ 66	Resin	-20 ~ 80	65M n	Nitr ile Rub ber