



Medium Bearing Series

LM □ RAUU-LM12RAUULMUDM12LMD12-d12

参数信息:



Model No. :

YTP (nickel plated) :	LM12RAUU
MISUMI (nickel plated) :	LMUDM12
YHDA (nickel plated) :	LMD12-d12

NUMBER OF BALL ROWS :

Column : 4

Boundary dimensions :

INSCRIBED CIRCLE DIAMETER _{dr} :	12
INSCRIBED CIRCLE DIAMETER TOLERANCE :	0-0.010
OUTER DIAMETER _D :	21
Outer DiameterTolerance :	0-0.016
Length _L :	47
LengthTolerance :	± 0.3
OUTER LOCKING GROOVE _B :	32.6
OUTER LOCKING GROOVE _B TOLERANCE :	0-0.30
OUTER LOCKING GROOVE _{D1} :	20
W :	1.3
Radial runout(MAX.) :	0.015

Basic Load Rating :

C(kgf) : 63.5

Co(kgf) : 81.5

Weight :

(g) : 54

介绍:

Model No.	Producti on Standards	Outer Coving			Balls		Retainer		Seals Material	
		Material	Hardness (HRC)	Treatmen t Of Surfaces	Material	Hardness (HRC)	Material	Holder Working Temperature	Skele ton	Rub ber
LM □ RUU	GB/T169 40-2012	GCr15	60 ~ 64	-	GCr15	61 ~ 66	Resin	-20 ~ 80	65M n	Nitr ile Rub ber
LM □ RAUU	GB/T169 40-2012	GCr15	60 ~ 64	Electroles s Nickel Plating	GCr15	61 ~ 66	Resin	-20 ~ 80	65M n	Nitr ile Rub ber