



Medium Bearing Series

LM RAUU-LM13RAUULMUDM13LMD12-d13

参数信息:



Model No. :

YTP (nickel plated) :	LM13RA UU
MISUMI (nickel plated) :	LMUDM 13
YHDA (nickel plated) :	LMD12-d 13

NUMBER OF BALL  
ROWS :

Column :	4
----------	---

Boundary  
dimensions :

INSCRIBED CIRCLE DIAMETER <sub>dr</sub> :	13
INSCRIBED CIRCLE DIAMETER TOLERANCE :	0-0.010
OUTER DIAMETER <sub>D</sub> :	23
Outer DiameterTolerance :	0-0.016
Length <sub>L</sub> :	47
LengthTolerance :	± 0.3
OUTER LOCKING GROOVE <sub>B</sub> :	32.6
OUTER LOCKING G ROOVE <sub>TOLERANCE</sub> :	0-0.30
OUTER LOCKING GROOVE <sub>D1</sub> :	22
W :	1.3
Radial runout(MAX.) :	0.015

Basic Load Rating :

C(kgf) :	64
----------	----

Co(kgf) : 82.6

Weight :

(g) : 69

介绍:

Model No.	Producti on Standards	Outer Coving			Balls		Retainer		Seals Material	
		Material	Hardness ( HRC )	Treatmen t Of Surfaces	Material	Hardness ( HRC )	Material	Holder Working Temperature	Skele ton	Rub ber
LM RUU	GB/T169 40-2012	GCr15	60 ~ 64	-	GCr15	61 ~ 66	Resin	-20 ~ 80	65M n	Nitr ile Rub ber
LM RAUU	GB/T169 40-2012	GCr15	60 ~ 64	Electroles s Nickel Plating	GCr15	61 ~ 66	Resin	-20 ~ 80	65M n	Nitr ile Rub ber