



Medium Bearing Series

LM RAUU-LM16RAUULMUDM16LMD12-d16

参数信息:



Model No. :

YTP (nickel plated) :	LM16RA UU
MISUMI (nickel plated) :	LMUDM 16
YHDA (nickel plated) :	LMD12-d 16

NUMBER OF BALL  
ROWS :

Column :	5
----------	---

Boundary  
dimensions :

INSCRIBED CIRCLE  
DIAMETER<sub>dr</sub> :

16

INSCRIBED CIRCLE  
DIAMETER  
TOLERANCE :

0-0.010

OUTER  
DIAMETER<sub>D</sub> :

28

Outer  
DiameterTolerance :

0-0.016

Length<sub>L</sub> :

56

LengthTolerance :

± 0.3

OUTER LOCKING  
GROOVE<sub>B</sub> :

38.2

OUTER LOCKING G  
ROOVETOLERANCE  
:

0-0.30

OUTER LOCKING  
GROOVE<sub>D1</sub> :

27

W :

1.6

Radial  
runout(MAX.) :

0.015

Basic Load Rating :

C(kgf) :	116.5
----------	-------

Co(kgf) : 144.8

Weight :

(g) : 112

介绍:

Model No.	Producti on Standards	Outer Coving			Balls		Retainer		Seals Material	
		Material	Hardness ( HRC )	Treatmen t Of Surfaces	Material	Hardness ( HRC )	Material	Holder Working Temperature	Skele ton	Rub ber
LM RUU	GB/T169 40-2012	GCr15	60 ~ 64	-	GCr15	61 ~ 66	Resin	-20 ~ 80	65M n	Nitr ile Rub ber
LM RAUU	GB/T169 40-2012	GCr15	60 ~ 64	Electroles s Nickel Plating	GCr15	61 ~ 66	Resin	-20 ~ 80	65M n	Nitr ile Rub ber