



Medium Bearing Series

LM □ RAUU-LM20RAUULMUDM20LMD12-d20

参数信息:



Model No. :

YTP (nickel plated) :	LM20RA UU
MISUMI (nickel plated) :	LMUDM 20
YHDA (nickel plated) :	LMD12-d 20

NUMBER OF BALL
ROWS :

Column :	5
----------	---

Boundary
dimensions :

INSCRIBED CIRCLE DIAMETER _{dr} :	20
INSCRIBED CIRCLE DIAMETER TOLERANCE :	0-0.012
OUTER DIAMETER _D :	32
Outer DiameterTolerance :	0-0.019
Length _L :	65
LengthTolerance :	±0.3
OUTER LOCKING GROOVE _B :	43.2
OUTER LOCKING G ROOVE _{TOLERANCE} :	0-0.30
OUTER LOCKING GROOVE _{D1} :	30.5
W :	1.6
Radial runout(MAX.) :	0.02
Basic Load Rating :	
C(kgf) :	155.5

Co(kgf) : 206.8

Weight :

(g) : 152

介绍:

Model No.	Producti on Standards	Outer Coving			Balls		Retainer		Seals Material	
		Material	Hardness (HRC)	Treatmen t Of Surfaces	Material	Hardness (HRC)	Material	Holder Working Temperature°C	Skele ton	Rub ber
LM □ RUU	GB/T169 40-2012	GCr15	60~64	-	GCr15	61~66	Resin	-20~80	65M n	Nitr ile Rub ber
LM □ RAUU	GB/T169 40-2012	GCr15	60~64	Electroless Nickel Plating	GCr15	61~66	Resin	-20~80	65M n	Nitr ile Rub ber