



Medium Bearing Series

LM RAUU-LM30RAUULMUDM30LMD12-d30

参数信息:



Model No. :

YTP (nickel plated) :	LM30RA UU
MISUMI (nickel plated) :	LMUDM 30
YHDA (nickel plated) :	LMD12-d 30

NUMBER OF BALL
ROWS :

Column :	6
----------	---

Boundary
dimensions :

INSCRIBED CIRCLE DIAMETER _{dr} :	30
INSCRIBED CIRCLE DIAMETER TOLERANCE :	0-0.012
OUTER DIAMETER _D :	45
Outer DiameterTolerance :	0-0.019
Length _L :	90
LengthTolerance :	± 0.3
OUTER LOCKING GROOVE _B :	75
OUTER LOCKING G ROOVE _{TOLERANCE} :	0-0.40
OUTER LOCKING GROOVE _{D1} :	43
W :	1.85
Radial runout(MAX.) :	0.02

Basic Load Rating :

C(kgf) :	244
----------	-----

Co(kgf) : 397.5

Weight :

(g) : 422

介绍:

Model No.	Producti on Standards	Outer Coving			Balls		Retainer		Seals Material	
		Material	Hardness (HRC)	Treatmen t Of Surfaces	Material	Hardness (HRC)	Material	Holder Working Temperature	Skele ton	Rub ber
LM RUU	GB/T169 40-2012	GCr15	60 ~ 64	-	GCr15	61 ~ 66	Resin	-20 ~ 80	65M n	Nitr ile Rub ber
LM RAUU	GB/T169 40-2012	GCr15	60 ~ 64	Electroles s Nickel Plating	GCr15	61 ~ 66	Resin	-20 ~ 80	65M n	Nitr ile Rub ber