



Self-lubricating bearing series

LMHC □ LAUU-MX-**LMHC50LAUU-MXLHMCWM-MX50MX-LMQ22-d50**

参数信息:



Model No. :

YTP (nickel plated) :	LMHC50 LAUU- MX
MISUMI (nickel plated) :	LHMCW M-MX50
YHDA (nickel plated) :	MX-LMQ 22-d50

NUMBER OF BALL ROWS :

Column :	6
----------	---

Boundary dimensions :

INSCRIBED CIRCLE DIAMETER _{dr} :	50
INSCRIBED CIRCLE DIAMETER TOLERANCE :	0 -0.015
OUTER DIAMETER _D :	80
Outer DiameterTolerance :	0 -0.022
Length _L :	220
Length _{L1} :	192
LengthTolerance :	± 0.3
V :	14
I :	89.5
Flange _{D1} :	116
Flange _W :	86
Flange _H :	13
Flange _A :	80
Flange _F :	56
HOLE FOR ATTACHMENT _{d1} :	9

HOLE FOR
ATTACHMENTd2 : 14

HOLE FOR
ATTACHMENTh : 8.1

SOUAR- ENESS : 0.025

Eccentricity (MAX.) : 0.025

Basic Load Rating :

C(kgf) : 608

Co(kgf) : 1590

Weight :

(g) : 3500

介绍:

Model No.	Producti on Standards	Outer Coving			Balls		Retainer		Seals Material	
		Material	Hardness (HRC)	Treatmen t Of Surfaces	Material	Hardness (HRC)	Material	Holder Working Temperature	Skeleton	Rubber
LMHC □ LUU-MX	GB/T169 40-2012	GCr15	60 ~ 64	-	GCr15	61 ~ 66	Resin	-20 ~ 80	65Mn	Nitrile Rubber
LMHC □ LAU U-MX	GB/T169 40-2012	GCr15	60 ~ 64	Electroless Nickel Plating	GCr15	61 ~ 66	Resin	-20 ~ 80	65Mn	Nitrile Rubber

Note: The apertures of 35, 40, and 50 are not produced and are for reference only.