

Compact bearing series

LMCFP LAUU-LMCFP16LAUULML53-d16

参数信息:

Model No. :

YTP (nickel plated) : LMCFP16  
LAUU

YHDA (nickel plated) : LML53-d1  
6

NUMBER OF BALL  
ROWS :

Column : 6

Boundary  
dimensions :

INSCRIBED CIRCLE DIAMETER<sub>dr</sub> : 16

INSCRIBED CIRCLE DIAMETER TOLERANCE : 0-0.010

OUTER DIAMETER<sub>D</sub> : 26

Outer DiameterTolerance : 0-0.016

Length<sub>L</sub> : 70

LengthTolerance : ± 0.3

I : 6

Flange<sub>D1</sub> : 44

Flange<sub>H</sub> : 6

Flange : 36

HOLE FOR ATTACHMENT<sub>d1</sub> : 4.5

HOLE FOR ATTACHMENT<sub>d2</sub> : 7.5

HOLE FOR ATTACHMENT<sub>h</sub> : 4.1

HOLE FOR ATTACHMENT<sub>r</sub> : 3.75

SOUAR- ENESS : 0.015

Eccentricity (MAX.) : 0.015

Basic Load Rating :

C(kgf) : 96.5

Co(kgf) : 143

Weight :

(g) : 154

介绍:

Model No.	Production Standards	Outer Coving			Balls		Retainer		Seals Material	
		Material	Hardness ( HRC )	Treatment Of Surfaces	Material	Hardness ( HRC )	Material	Holder Working Temperature	Skeleton	Rubber
LMCFP LUU	GB/T16940-2012	GCr15	60 ~ 64	-	GCr15	61 ~ 66	Resin	-20 ~ 80	65Mn	Nitrile Rubber
LMCFP LAUU	GB/T16940-2012	GCr15	60 ~ 64	Electroless Nickel Plating	GCr15	61 ~ 66	Resin	-20 ~ 80	65Mn	Nitrile Rubber

Note: Not produced, for reference only.