



Triple lengthened bearing series

LMKP TM-LMKP6TMLHKNL6

参数信息:



model :

YTP (Steel Protection) :	LMKP6T M
MISUMI (Steel Insurance) :	LHKISNL F6
NUMBER OF BALL ROWS :	
Column :	4
Boundary dimensions :	
INSCRIBED CIRCLE DIAMETER _{dr} :	6
INSCRIBED CIRCLE DIAMETER TOLERANCE :	0-0.012
OUTER DIAMETER _D :	15
Outer DiameterTolerance :	0-0.013
Length _L :	49
LengthTolerance :	± 0.3
I :	5
Flange _{D1} :	32
Flange _K :	25
Flange _H :	5
Flange :	24
HOLE FOR ATTACHMENT _{d1} :	3.5
HOLE FOR ATTACHMENT _{d2} :	6
HOLE FOR ATTACHMENT _h :	3.1
SOUAR- ENESS :	0.02
Eccentricity (MAX.) :	0.02

Basic Load Rating :

C(kgf) : 33

Co(kgf) : 54

Weight :

(g) : 58

介绍:

Model	Producti on standard	Shell			rolling ball		Retainer		Accessory (seal) material	
		Material	Hardness (HRC)	Surface treatment	Material	Hardness (HRC)	Material	Using te mperatur e	Skeleton	Rubber
LMKP TUU	GB/T169 40-2012	GCr15	60 ~ 64	-	GCr15	61 ~ 66	Resin	-20 ~ 80	65Mn	Nitrile rubber
LMKP TAUU	GB/T169 40-2012	GCr15	60 ~ 64	Electroless nickel plating	GCr15	61 ~ 66	Resin	-20 ~ 80	65Mn	Nitrile rubber
LMKP TM	GB/T169 40-2012	GCr15	60 ~ 64	-	GCr15	61 ~ 66	304 stainless steel	-20 ~ 80	65Mn	-
LMKP TAM	GB/T169 40-2012	GCr15	60 ~ 64	Electroless nickel plating	GCr15	61 ~ 66	304 stainless steel	-20 ~ 80	65Mn	-

Note: The inner holes are 6, 8, 10, 13, 35, 40, not produced, for reference only.