



Triple lengthened bearing series

LMHP TAM-LMHP20TAMLHKICLF20

参数信息:



Model No. :

YTP (steel protection nickel plating) :	LMHP20 TAM
MISUMI (steel protection nickel plating) :	LHKICLF 20

NUMBER OF BALL ROWS :

Column : 5

Boundary dimensions :

INSCRIBED CIRCLE DIAMETER _{dr} :	20
INSCRIBED CIRCLE DIAMETER TOLERANCE :	0-0.018
OUTER DIAMETER _{Dr} :	40
Outer Diameter Tolerance :	0-0.019
Length _L :	120
Length Tolerance :	± 0.3
I :	8
Flange _{D1} :	62
Flange _W :	46
Flange _H :	8
Flange _A :	40
Flange _F :	32
HOLE FOR ATTACHMENT _{d1} :	5.5
HOLE FOR ATTACHMENT _{d2} :	9
HOLE FOR ATTACHMENT _h :	5.1

SOUAR- ENESS :	0.025
Eccentricity (MAX.) :	0.025
Basic Load Rating :	
C(kgf) :	143
Co(kgf) :	280
Weight :	
(g) :	724

介绍:

Model	Producti on standard	Shell			rolling ball		Retainer		Accessory (seal) material	
		Material	Hardness (HRC)	Surface treatment	Material	Hardness (HRC)	Material	Using te mperatur e	Skeleton	Rubber
LMHP TUU	GB/T169 40-2012	GCr15	60 ~ 64	-	GCr15	61 ~ 66	Resin	-20 ~ 80	65Mn	Nitrile rubber
LMHP TAUU	GB/T169 40-2012	GCr15	60 ~ 64	Electroless nickel plating	GCr15	61 ~ 66	Resin	-20 ~ 80	65Mn	Nitrile rubber
LMHP TM	GB/T169 40-2012	GCr15	60 ~ 64	-	GCr15	61 ~ 66	304 stainless steel	-20 ~ 80	65Mn	-
LMHP TAM	GB/T169 40-2012	GCr15	60 ~ 64	Electroless nickel plating	GCr15	61 ~ 66	304 stainless steel	-20 ~ 80	65Mn	-

Note: The inner holes are 6, 8, 10, 13, 35, 40, not produced, for reference only.