



Linear bearing standard series

LM -LM6LMU6-NLMC01-d6

参数信息:



| | |
|-----------|--------------|
| YTP : | LM6 |
| MISUMI : | LMU6-N |
| YHDA : | LMC01-d 6 |
| (g) : | 4 |
| W : | 7.6 |
| C(kgf) : | 6 |
| Co(kgf) : | 0-0.009 |

介绍:

| Model | Production standard | Shell | | | rolling ball | | Retainer | | Accessory (seal) material | |
|-----------|---------------------|----------|----------------|----------------------------|--------------|----------------|---------------------|-------------------|---------------------------|----------------|
| | | Material | Hardness (HRC) | Surface treatment | Material | Hardness (HRC) | Material | Using temperature | Skeleton | Rubber |
| LM | GB/T16940-2012 | GCr15 | 60 ~ 64 | - | GCr15 | 61 ~ 66 | Resin | -20 ~ 80 | 65Mn | - |
| LM UU | GB/T16940-2012 | GCr15 | 60 ~ 64 | - | GCr15 | 61 ~ 66 | Resin | -20 ~ 80 | 65Mn | Nitrile rubber |
| LM AUU | GB/T16940-2012 | GCr15 | 60 ~ 64 | Electroless nickel plating | GCr15 | 61 ~ 66 | Resin | -20 ~ 80 | 65Mn | Nitrile rubber |
| LM M | GB/T16940-2012 | GCr15 | 60 ~ 64 | - | GCr15 | 61 ~ 66 | 304 stainless steel | -20 ~ 150 | 65Mn | - |

| | | | | | | | | | | |
|----------|--------------------|-------|---------|----------------------------------|-------|---------|---------------------------|-----------|------|---|
| LM AM | GB/T16940- 2012 | GCr15 | 60 ~ 64 | Electroless nickel plating | GCr15 | 61 ~ 66 | 304 stainless steel | -20 ~ 150 | 65Mn | - |
|----------|--------------------|-------|---------|----------------------------------|-------|---------|---------------------------|-----------|------|---|