



Linear flange bearing series

LMEK LUU-LMEK8LUUKBK8GWUU

参数信息:



Model No. :

| | |
|----------|--------------|
| YTP : | LMEK8L UU |
| NB : | KBK8GW UU |
| SAMICK : | LMEK8L UU |

NUMBER OF BALL
ROWS :

| | |
|----------|---|
| Column : | 4 |
|----------|---|

Weight :

| | |
|-------|----|
| (g) : | 51 |
|-------|----|

Boundary
dimensions :

| | |
|--|------------------|
| INSCRIBED CIRCLE DIAMETER d_r : | 8 |
| Inscribed Circle Diameter Tolerance : | +0.009 -0.001 |
| OUTER DIAMETER D_1 : | 16 |
| Outer Diameter Tolerance : | 0 -0.009 |
| Length L : | 46 |
| LENGTH TOLERANCE : | ± 0.3 |
| Flange D_1 : | 32 |
| Flange K : | 25 |
| Flange H : | 5 |
| Flange : | 24 |
| HOLE FOR ATTACHMENT d_1 : | 3.5 |
| HOLE FOR ATTACHMENT d_2 : | 6 |
| HOLE FOR | 3.1 |

ATTACHMENT h :

SOUAR- ENESS : 0.015

Eccentricity (MAX.) : 0.015

Basic Load Rating :

C(kgf) : 43

Co(kgf) : 82

介绍:

| Model No. | Producti on Standards | Outer Coving | | | Balls | | Retainer | | Seals Material | |
|-----------|-----------------------|--------------|------------------|----------------------------|----------|------------------|----------|----------------------------|----------------|----------------|
| | | Material | Hardness (HRC) | Treatmen t Of Surfaces | Material | Hardness (HRC) | Material | Holder Working Temperature | Skeleton | Rubber |
| LMEK LUU | GB/T169 40-2012 | GCr15 | 60 ~ 64 | - | GCr15 | 61 ~ 66 | Resin | -20 ~ 80 | 65Mn | Nitrile Rubber |
| LMEK LAUU | GB/T169 40-2012 | GCr15 | 60 ~ 64 | Electroless Nickel Plating | GCr15 | 61 ~ 66 | Resin | -20 ~ 80 | 65Mn | Nitrile Rubber |